

TRB142*1****

INDUSTRIAL RUGGED LTE RS232 GATEWAY



CONNECTIVITY

4G/LTE (Cat 1), 3G, 2G

SERIAL PORT

Equipped with RS232 for serial communication

COMPACTNESS

Small size, easy installation

DURABILITY

Rugged aluminum housing

9-30V

Wide range of supported power supply voltages

RMS

Compatible with Teltonika Remote Management System

TRB142

PRODUCT DESCRIPTION

// TRB142 comes with a widely used RS232 interface for remote device management.

// It is equipped with mission-critical LTE Cat 1 capabilities and software based on OpenWRT, hence offering a high degree of customization.

// Just like the other TRB series products, it provides a wide range of software features such as SMS control, VPN, IPsec, Firewall, and FOTA support.

// This gateway is durable, offers a wide range of power supply voltages, and is compatible with Teltonika Networks Remote Management System (RMS).



FRONT VIEW

BACK VIEW

Power LED



Power socket

RS232 connector

Mobile antenna connector



USB connector

Reset button

KEY FEATURES

HARDWARE

| | |
|------------------------|--|
| Mobile | 4G/LTE (Cat 1), 3G, 2G |
| CPU | Qualcomm, ARM Cortex A7, 1.2 GHz |
| Memory | 512 MBytes Flash (70 MBytes for userspace), 128 MBytes RAM (50 MBytes for userspace) |
| Powering option | 4pin power socket, 9-30 VDC |
| SIM | 1 x Internal SIM holder (2FF) |
| Antenna connectors | 1 x SMA for mobile |
| Inputs/Outputs | On 4pin socket |
| Serial | 1 x RS232 |
| Other | 1 x Micro USB slave |
| Status LEDs | 3 x Connection type, 5 x Signal strength, 1 x Power |
| Operating temperature | -40° C to 75° C |
| Housing | Aluminium housing with DIN rail mounting option |
| Dimensions (W x H x D) | 75 x 25 x 65 mm |
| Weight | 135 g |

SOFTWARE

| | |
|---------------------------|--|
| Operating system | RutOS |
| Network protocols | TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSLv3, TLS 1.3, ARP, PPP, DHCP, Telnet |
| Monitoring and Management | WEB UI, CLI, SSH, SMS, TR-069, SNMP, JSON-RPC, MQTT, RMS |
| Connection monitoring | Ping Reboot, Wget reboot, Periodic Reboot, LCP and ICMP for link inspection |
| Cloud solutions | RMS, FOTA, Telenor, Azure IoT Hub, Cloud of Things, Cumulocity, ThingWorx |
| Modbus | TCP slave, TCP master, RTU master, RTU gateway, Modbus over MQTT |
| Serial | Console, Over IP, Modem, NTRIP, Modbus |

RMS

RMS | REMOTE MANAGEMENT SYSTEM
COMPATIBLE WITH TRB142
 MANAGEMENT | ALERTS | CONFIGURATION | ACCESS | FOTA



SOCIAL

